15. YEAR IN THE PRODUCTION OF CONSTRUCTION MACHINERY

PASHA MACHINE CONCRETE · SHOTCRETE · SCREED · PLASTER· GROUT

SERAYMAX

MORTAR SPRAYING MACHINERY



IT IS OUR JOB TO MANUFACTURE CONSTRUCTION MACHINERY

SPRAYMAX

SGFGS



www.pashaturkiye.com

SPRAYMAX SERIES MORTAR SPRAYING MACHINERY

is available longer than 12 years as conclusive solutions for the mortar spraying and conveying technologies. All the current technological improvements are used in the design and production of the machinery. The SPRAYMAX is the symbol of QUALITY, INNOVATION and TRUST.

ELECTRICAL MACHINE

It is triggered by electrical motor. Its innovative technology is economic. It reaches the maximum power consuming the lowest electricity. It does not consume diesel oil for more power. It is environment friendly.

MIXER and PUMP: IMPROVED TECHNOLOGY POWERFUL-ROBUST-DURABLE

It is a very unique mortar spraying machine which does not have any equivalent. It is the machine with no limits, working at full performance and with many additions. It can pump all kinds of sand and similar materials with the approprite grain size and viscosity which will not block the hose with 35 mm inner diameter. As it is very powerful, the stop and re-starts does not block the pump even at longer or higher distance. The mixer is independent from the pump and works continuously by user control. It applies the mortar smoothly and it does not fall off the surface. The mixer makes homogenous mixes and the materials are not wasted. It also prevents blocking the pump or the hose.



SPRAYMAX Series





PME-40 MAX

It is a very unique mortar spraying machine with many additions and advantages. It is designed in particularly for both internal and external mortar spraying applications with site mixes. It is a great product modernizing the old and traditional methods of the mortar spraying application in a way which is more useful, practical and cost effective. It has the shortest mixer level with 1.10 m filling height from the ground. It has the safety sensor for stopping the mixer paddles when the grid is opened. It supports grain size up to 7 mm. It has the removable support-tire for easy movement at the construction site.

It is ideal for the spraying application of site mixes (ex. cement-sand), or dry premixed interior and exterior rendering, colored mortar, limestone mortar, base coat, light wall mortar, ornamental plaster, ready-mix plaster, liquid screed and for filling and grouting works.

PME-40 MAX Series TECHNICAL FEATURES

FIVIL-40 MAX Selies I LCIIIIICAL I LAIGNES	
FEATURES	
Trigger	Electrical, 380 V - 50 Hz
Motor Power	9.9 kW
Compressor Output	350 lt/min @ 5.5 bar
Spraying Output	35 lt/min
Grain Size Supported	0-10 mm
Grain Size Recommended	0 - 5 mm
Mixer Volume	212 lt
Mixer Fillling Height	1100 mm
Remote Control Option	Available
STRAT/STOP Control on the Spray Gun	Available
Grid - Safety Sensor to START/STOP the Paddles	Available
Emergency STOP	Available
Trailer	2 axle connected and 1 support wheels
Vehicle Connection	Available
Dimensions (LxWxH)	2750 x 1500 x 1250 mm
Weight	550 kg

SERAYMAX

www.pashaturkiye.com

IT IS OUR JOB TO MANUFACTURE CONSTRUCTION MACHINERY

15. YEAR IN THE PRODUCTION OF CONSTRUCTION MACHINERY

CONCRETE · SHOTCRETE · SCREED · PLASTER · GROUT

