

Mobile Diesel Light Tower PK4022LDW



52 hrs lighting time with wide fuel tank displacement.

Durable for any kind of air condition, full protection against to external factor with elektrostatic colored body.

Galvanized coating tower durable against to corrosion, tower earth connection, jacks and supported front wheel.

Galvanized coating tower durable against to corrosion, tower earth connection, jacks and supported front wheel.

Easy balanceable specification with 4 units jacks at the rough terrain and windy weather.

For external needs, 2 units 220VAC plugs with 10A and 16A safety fuse.

Separate oriented control panel; informing to user with warning and attitude indicator during first working and attitude indicator during first working and using.

High intensity of illumination with 4 units 1000w metal Halide lamps.

Heated spark plug system during working without problem at the cold weather.

Protection feature against to engine damage with automatic engine stop circuit against to low oil level, movement of cooling water.

Technical Specifications

Engine		
Mark	Lombardini Diesel	--
Type	Water Cooled, 4 Stroke, 3 Cylinder	--
Power	16.5 - 22	kW - HP
Displacement	1028	cm ³
Rotation	3000	rpm
Fuel Tank	100	lt
Output	10 (220 V)-50	kVA-Hz
Fuel Consumption	1.9	l/h
Dimensions (WxLxH)	1500x4300x1700	mm
Transportation Weight	740	kg
Maximum Tower Altitude	9	m
Lamp Power	4x1000 Metal Halide	W
Lighting Area	30400 (5 Lumen/m ²)	--
Noise Level	70	dBA
Rotation of Tower	Mechanical	--